

CORRECTED VERSION

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
22 September 2005 (22.09.2005)


PCT

(10) International Publication Number
WO 2005/088121 A2

- (51) International Patent Classification⁷: F03D
- (21) International Application Number: PCT/DK2005/000181
- (22) International Filing Date: 17 March 2005 (17.03.2005)
- (25) Filing Language: Danish
- (26) Publication Language: English
- (30) Priority Data:
PA 2004 00429 17 March 2004 (17.03.2004) DK
- (74) Agents: JØRGENSEN, Bjørn, Barker et al.; International Patent-Bureau A/S, Høje Taastrup Boulevard 23, DK-2630 Taastrup (DK).
- (81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SM, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM,

[Continued on next page]

(54) Title: A METHOD OF CONTROLLING A WINDMILL, ESPECIALLY IN STAND-ALONE OPERATION, AND A WINDMILL



(57) Abstract: A windmill comprising a rotor having a substantially horizontal axis of rotation (1a) and at least two blades (4) extending along a respective blade axis, about which the blade can be rotated to an adjustment angle for the blade, and a blade adjusting device (11, 13) for adjusting a common basic angle of adjustment for the blades (4), said windmill further comprising means (14) for detecting the size of the basic angle of adjustment, means for detecting the load on the windmill and means (15-22) for detecting the deflection of the blade, preferably in the direction of the axis of the rotor (1a), is controlled according to the invention by adjustment of the basic angle of adjustment, a control signal for the blade adjusting device being provided in dependency of the load and the wind speed, and, as a measure for the wind speed, the deflection α of the blade is used, preferably in the direction of the rotational axis (1a) of the rotor.

WO 2005/088121 A2



ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

(48) Date of publication of this corrected version:

10 November 2005

(15) Information about Correction:

see PCT Gazette No. 45/2005 of 10 November 2005, Section II

Published:

— without international search report and to be republished upon receipt of that report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.